



Reliable industrial-grade Bluetooth® Low Energy tag for industrial identification and location applications

Beontag Viking Micro, with its small form factor, is designed for high-volume, small industrial asset tracking use cases in harsh industrial environments using Bluetooth® Low Energy (BLE) technology. It has a non-replaceable coin cell battery offering a lifetime of up to 8 years in typical applications.

It supports Eddystone™ (UID, URL, TLM) and iBeacon™ open standard frame formats, ensuring straightforward implementation across a wide range of BLE applications.

DIMENSIONS

Viking Micro CR 2032 – 36X26X6 mm

Viking Micro CR 2050 – 36X26X8 mm



ASSET
MANAGEMENT



LOGISTICS AND
SUPPLY CHAIN



INDUSTRIAL
MANUFACTURING



AUTOMOTIVE



BLE TAG

Viking Micro



Electrical specifications

Device type

Bluetooth® Low Energy tag, Battery powered

Wireless interface protocol

Bluetooth® 5.3

Compliance (Declaration of Conformity)

Europe (CE), UK (UKCA), USA (FCC), Canada (IC)

Operational frequency band

2.4GHz ISM: 2402 - 2480 MHz

System-on-Chip

InPlay IN100

Configuration

One-time configured at ordering

Sensors

Built-in temperature sensor*, hall switch, battery Voltage

Max transmit power

+4 dBm

Read range**

70m at 0dBm / 230 ft

Battery capacity

non-replaceable coin cell

CR2032 220mAh

CR2050 380mAh

Applicable surface materials


Can operate attached to any surface

*Temperature sensor is located inside the housing, which limits real time measurement of the ambient temperature.

** Read ranges are theoretical values that are calculated for non-reflective environment. Different surface materials may influence performance.



Mechanical specifications



Housing material

High quality PC+ASA

Color: dark grey

Pantone 433U

Weight

CR2032: 7g

CR2050: 9g

Packaging amount and box size

CR2032: 30 pieces in box 30x40x250mm

Dimensions

CR2032: 36 x 26 x 6mm
/ 1.4 x 1.0 x 0.2inch

CR2050: 36 x 26 x 8mm
/ 1.4 x 1.0 x 0.3inch



Environmental resistance

Operating temperature

-20°C to +60°C / -4°F to +140°F

Water resistance

IP68, tested submerged at 1m for 5 hours

ESD immunity

±8 kV according to EN 61000-4-2 (air discharge)

±4 kV according to EN 61000-4-2 (contact discharge)

Chemical resistance***

No physical or performance changes in:

- 168h Motor oil exposure
- 48h Salt water (salinity 10%) exposure
- 48h Sulfuric acid (10%, pH 2) exposure
- 48h NaOH (10%, pH 13) exposure

Generally good resistance with moderate concentrations of acids, alcohols, alkalis, detergents, and cleaners.

Acetone should be avoided.

***Values are the best recommendations; resistance against environmental conditions depends on the combination of all influencing factors, exposure duration and chemical concentrations. Thus, product's final suitability for certain environmental conditions is recommended to be tested. Contact Confidex for more specific information.



Supported frames



Eddystone is a trademark of Google Inc
iBeacon is a trademark of Apple Inc.

Viking Micro tag utilizes Eddystone™ open standard frame format and/or iBeacon protocol, ensuring straightforward implementation on a wide range of Bluetooth® Low Energy devices.

Viking Micro is factory configured with customer-specific parameters to be used instantly with any third-party system. Vikings can also be personalized with a custom branded label to ease tag identification in the field.

Supported BLE advertisement beacon protocols:

- **Eddystone™-UID** frame broadcasts 16-byte Beacon ID composed of a 10-byte namespace and a 6-byte instance.

- **Eddystone™-TLM** frame broadcasts telemetry information (e.g. SoC voltage and temperature).
- **iBeacon** frame type supported with advertising 16 bytes UUID, 2 bytes Major, and 2 bytes Minor.
- **Manufacturer Specific data**

Expected lifetime****

Typical lifetime at 6s UID advertisement interval, 0dBm:

6 years with CR2032

8 years with CR2050

**** Beacon lifetime is optimized for long term use, however highly affected by operating mode parameters and ambient conditions. Configured TX power level and advertisement interval have influence on lifetime



Installation instructions

1. High performance acrylic adhesive

Mounting the tag with high performance acrylic adhesive can be used in most applications and surfaces. Clean and dry the surface to obtain the maximum bonding strength.

2. Mechanical fixing - Cable tie

Plastic or metallic cable ties can also be used for fixing Beontag Viking Micro at the middle of the tag. The maximum width of a cable tie is 4 mm.



Activation

The Beontag Viking Micro must be activated once by using a **magnet**.

To activate touch a magnet to the area on the front indicated:



Order informations

Product number: 3004729

Product name: Beontag Viking Micro CR2032 - Dark grey, customer specific configured and label. CR2032 coin cell

Product number: 3004941

Product name: Beontag Viking Micro CR2050 - Dark grey, customer specific configured and label. CR2050 coin cell.

For availability and additional information please write to contact@BLEbeontag.com

DISCLAIMER

THE MATERIALS, PRODUCTS AND SERVICES ARE SOLD SUBJECT TO ITS STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, BEONTAG AND ITS AFFILIATES MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN CONFIDEX STANDARD CONDITIONS OF SALE, CONFIDEX AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN.

Each user bears full responsibility for making its own determination as to the suitability of Beontag products, materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished systems incorporating Beontag products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Beontag.

About Beontag

From the science of graphic and label materials, RFID and wireless IoT enablers, we create solutions across the value chain to deliver digital transformation for businesses around the world.

Sustainability is at the core of what we do and we strongly believe that by substituting non-renewable materials and innovating through more sustainable and renewable products, we act as an ESG enabler for our customers' value chain.

Beontag is one of the world's leading providers of RFID and wireless IoT solutions, being present in more than 40 countries with 7 R&D centers and 2,000 employees, in constant development of technological and sustainable solutions designed to connect items, and gain efficiency and end-to-end traceability.

**CONTACT US FOR
MORE INFORMATIONS:
[beontag.com](https://www.beontag.com)**

The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience and the pictures and illustrations presented in this document are for illustration purposes only. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Beontag reserves the right to change its products and services at any time without notice.